



Fluxaf Mould Fix

Fluxaf Mould Fix is the ideal solution for quickly and effectively combating mold and scale on tiles, grout, and ceilings. Whether it's in the bathroom, shower, toilet, kitchen, basement, sauna, swimming pool, garage, or shed, Fluxaf Mould Fix swiftly eliminates stubborn black stains and restores the appearance of your surfaces. Thanks to its powerful bleaching action, the product removes gray and black mold spots, leaving your spaces feeling fresh and hygienic again.

Removes mold from:

- Walls
- Tiles
- Grout
- Ceilings

Applicable in:

- Bathrooms
- Showers
- Toilets
- Kitchens
- Basements
- Saunas
- Swimming pools
- Garages
- Sheds

Instructions:

1. Test a small, inconspicuous area of the surface for colorfastness and resistance before use.
2. Always wear gloves and protective clothing due to the bleaching effect. Be cautious of splashes on non-chlorine-resistant surfaces. If contact with these surfaces occurs, rinse immediately with water. Ensure proper ventilation and do not inhale the spray mist.
3. Do not remove mold before application.
4. Set the spray nozzle to the spray setting. Spray the surface from a distance of approximately 3-5 cm.
5. Allow the product to work for 10 minutes.
6. For heavy contamination, repeat the treatment after 10 minutes. For elastic joints (e.g., silicone sealant), it is recommended to apply the treatment twice. Note: Light elastic joints may show brown discoloration after use.
7. Thoroughly clean the sprayed surface with a sponge and water.
8. After use, return the spray nozzle to the non-spray position.

Attention! Do not use on textiles, carpets, (uncoated) metals, glossy paintwork, or tiles with a vulnerable or damaged glaze layer. These surfaces may discolor or become damaged. For safety, cover these surfaces before using Fluxaf Mould Fix. Do not use in combination with acids or other products. Fluxaf Mould Fix is intended solely for the removal of mold and is not suitable for other applications.

Efficiency:

Approximately 4-6 m² per liter on walls

Approximately 12-16 m² per liter on tile grout

Approximately 2-3 m² per liter on ceilings

Note! Coverage depends on the level of contamination

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.

Cleaning:

Clean tools with water.

Available quantities:

500 ml.

Shelf life:

The shelf life of Fluxaf Mould Fix is 2 years from the production date, provided the product is stored correctly. Store in a cool, dry place and protect from direct sunlight and freezing. After opening, seal the product properly and store it according to the mentioned guidelines.

Safety advice:

For extensive safety information, consult the MSDS.

MSDS can be downloaded at www.fluxaf.nl.

Admission number:

14179N/4514B