



Fluxaf Terrace Degreaser

Fluxaf Terrace Degreaser is a powerful and user-friendly solution for removing unwanted grey discoloration from wooden surfaces, such as furniture, floors, and garden furniture. This specially developed gel deeply penetrates the wood, effectively removing greying, dirt, and other contaminants caused by exposure to the elements. The product restores the wood's natural color and appearance without damaging the surface. Fluxaf Terrace Degreaser is ideal for both indoor and outdoor applications, offering an easy way to restore the shine of your wooden surfaces without the need for intensive sanding or using a pressure washer. For long-lasting results, the product can be perfectly combined with a protective wood stain or oil.

Applicable to:

- Sheds
- Decking
- Scaffolding
- Garden furniture
- Canopies
- Conservatories
- Fences
- Garden sheds
- Sheds

Suitable for:

- Douglas wood
- Larch wood
- Hardwood
- Pine wood
- Pine wood
- Oak wood
- Scaffolding wood

Instructions:

1. Protect metals and plants from direct contact and cover them with foil.
2. The surface must be clean, dry and sound. Remove dirt, dust, mould, algae and moss growth and loose parts. Sanding is not necessary.
3. Moisten the surface to be treated with water.
4. Stir the contents thoroughly.
5. Use a flat brush or roller. Apply in the longitudinal direction of the wood grain for a good finish.
6. Apply the gel generously.
7. Let it set for at least 20 minutes.
8. Brush the surface with a hard brush or broom and rinse with water. We do not recommend using a high-pressure cleaner as the hard jet can damage the wood.
9. After complete drying for at least 48 hours, the cleaned surface can be treated with a Lacq product of your choice.

Attention! Duration of wood protection depends on the quality of the wood, correct pre-treatment, execution of painting, maintenance, and intensity of load. Always do a test area first to see if you get the desired finish and this will vary on different wood.

Coverage:

Approximately 10 m² per litre.

Coverage always depends on the structure, suction of the wood, layer thickness, the tools used and application conditions.

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.

Drying Time:

Paintable:	Approx. .48 hours
Min. working temperature:	9 °C.
Max. processing temperature:	25 °C.

Contents:

Lacq Wood Degreaser contains biodegradable oxalic acid (<10%). The product is free of solvents, formaldehyde, chlorine compounds and amines.

Cleaning:

Cleaning tools with water.

Available Quantities:

2.5 litres.

Shelf life:

Store in a dry and frost-free room. Keep away from children.

Safety advice:

For extensive safety information, consult the MSDS.
MSDS can be downloaded at www.fluxaf.nl.