



Lacq Edge Sealer

Lacq offers the right wood protection for every job! Lacq Edge Sealer is a water-based wood protection for untreated cuts and holes in treated wood. The product offers protection against penetrating moisture and also serves as an additional protective layer before applying the primer and finishing coat to prevent strong suction.

Applicable to:

- Untreated sawn pieces
- End grain edges

Suitable for:

- General building timbers
- Decking & Terrace
- Garden timbers
- Fencing timbers

Application on untreated wood:

1. The surface must be clean, dry and sound. Remove dirt, dust, mould, algae and moss growth and loose parts. Sanding is not necessary, only when a smooth result is desired.
2. Degreasing and cleaning with [Fluxaf Pro-Clean](#).
3. Stir the contents thoroughly.
4. Use a flat brush or roller suitable for water-based paint. Apply in the longitudinal direction of the wood grain for a good finish.
5. Thinning is not necessary, though you may want to thin it with up to 5% water.
6. Apply one layer.
7. The primer coat and finishing coat can only be applied after complete drying for about 2 hours.

Caution! Lacq Edge Sealer is not to be used in ground contact applications or to recoat pressure treated wood surfaces or as a replacement for pressure treatment. Hazardous to bees. Do not use on beehives or beekeeping

Caution! Duration of wood protection depends on the quality of the wood, correct pre-treatment, execution of painting, maintenance and intensity of load. Always put a test piece on first to see if you get the desired finish. After all, this can vary from one type of wood to another.

Tools:

Flat brush or roller suitable for water-based paint.

Yield:

Approximately 6-7 m² per litre.

Caution! Yield always depends on the structure, suction of the wood, layer thickness, the tools used and application conditions.

Drying time:

Drying times depend on the applied layer and ambient temperature. Optimal conditions are 20 °C.

Dust-dry:	approx. 1 hours
Paintable:	approx. 2 hours
Min. working temperature:	10 °C.
Max. processing temperature:	30 °C.

Cleaning:

Clean tools with water.

Caution! There is a danger of scalding and fire when using textiles. Always pour over with water and allow to dry thoroughly.

Available quantities:

500 ml.

Available colours:

White & Clear.

Please note! The type of wood and the number of coats applied may influence the colour result. We therefore recommend always putting on a test piece first to assess the result.

Shelf life:

Close airtight after use and turn over briefly to fill the rim for a good seal. Store 2 years in original unopened packaging, frost-free, in a dry place (temperature between 5°C and 35°C).

Safety advice:

Keep out of the reach of children. The product is not to be used in ground contact applications or to recoat pressure treated wood surfaces or as a replacement for pressure treatment. Any pressure treated timber that has been rip sawn, thickened or planed must be returned for pressure treatment to ensure correct protection. Protect from freezing. Hazardous to bees. Do not use on beehives or beekeeping. For detailed safety information, refer to the MSDS. MSDS can be downloaded at www.lacq.eu.

Customised advice:

For any advice, please contact the technical team on 0344 633 336.